

HARVIA MODERNA

HVE804XEM

Harvia Moderna, the royalty of electric sauna heaters, will heat up your sauna quickly. Thanks to the digital XE control, it is easy to heat up your sauna to your exact preference, to the accuracy of a single degree.



Advantages

- The stylish Moderna XE with digital control, mounted on the wall, will heat up your sauna quickly.
- The Moderna XE electric sauna heater a range of features and it is easy to install in a new or old sauna. It does not require a separate control unit installed in a dry room. All connections, such as the control panel, door sensor and temperature sensor and connected directly to the heater.
- The Xenio control panel is equipped with illuminated touch keys and a digital display.
- Use the Xenio XE control panel to switch on the heater at any time to reach the desired temperature, to adjust the lighting and to monitor the temperature.
- The Moderna XE model is easy to update to be compatible with MyHarvia with the Xenio WiFi accessory, enabling you to control your sauna functions with your phone. Learn my about the MyHarvia application at www.myharvia.com.

Features

Main material : Steel

H x W x D : 580.0 x 410.0 x 310.0 mm

Net weight (kg) : 14.0

Installation location : Floor

ID	GTIN	Output (kW)	Sauna room size min - max m3
HVE804XEM	6417659028080	8 kW	7.0-12.0

Related products


HSW1


SP311


SP312


SP315


SP319



Spare parts

Product	ID	Pcs
Airflow spoiler Moderna	SPZSM-40	
Heating element 2670W 230V	SPZSK-710	3
Circuit board max. 11 kW 230VAC XE/XW heaters	SP683	1
Data cable RJ16 4P4C 5 m RJ16 black	SP311	1
Control panel Harvia Xenio Wifi black	SP694	1
power switch and cover, white	SPZSK-684	1
Control panel Xenio Harvia heaters (XE- models, CX170, CX110) black	SP380	1
Temperature sensor (135C limiter) white	SP247	1

Technical details

Technical data	Type / attribute	HVE804XEM
	Color	Black
	Power output	8 kW
	Stone sizes	Ø5–10 cm
	Stone amount (kg)	20
Dimensions	Product width	410
	Product height	580
	Product depth (mm)	310
	Net weight (kg)	14
	Gross weight	15.1
	Package width	410
	Package height	630
	Package depth	310
Safety and installation dimensions	Safety distance front (non-combustible materials)	30
	Safety distance front (combustible materials)	30
	Safety distance right side (combustible materials)	70
	Safety distance right side non-combustible materials	70
	Safety distance left side (combustible materials)	70
	Safety distance left side non-combustible materials	70
	Safety distance side (non-combustible materials)	70
	safety distance to the side wall (combustible materials)	70
	Safety distance (Ceiling)	1100
	Room min. height(depends on connections and therefore from output, star/delta)	1900
	Installation opening height	1900
	Installation opening width	550
	Installation opening depth	340