

Wood burning heater Harvia Linear 22 GreenFlame

WKLI20GM

An elegant wood-burning heater for medium-sized saunas, Harvia Linear 22 GreenFlame ensures a clean and stable fire behind a large glass door, which creates a relaxing atmosphere in the sauna. You can now bath with lower emissions than ever before.



Advantages

- Linear GreenFlame is a wood-burning heater with a large glass hatch and advanced combustion technology to ensure a clean burn and long service life
- 20% lower particulate emissions and 70% lower carbon monoxide emissions
- 90% larger glass hatch
- The matte black colour and elegant design create a modern look in the sauna.
- The durable structure and replaceable internals ensure a long service life (flame guide panels at sides and back)

Features

Main material : Steel

H x W x D : 770.0 x 450.0 x 510.0 mm

Net weight (kg) : 66.0

Stone amount (kg) : 40.0

ID	GTIN	Power	Sauna room size min - max m3
WKLI20GM	6417659041430	15.7 kW	9.0-18.0



Spare parts

Product	ID	Pcs
Adjustable legs for LG150/SL	SPZKIP-918	
Hinge pin, long	SP675	
Spare part, latching pin	SP674	
Glass kit, GreenFlame	SP676	1
Ashtray black, sauna heaters	SP682	
Connection pipe 200 mm	SPZKIP-130	1
Big glass door	SP673	
Handle for door Legend GF	SP687	
Cast-iron grating 135x290mm, sauna heaters	SPZKIP-10	
Cap for smoke hole (Ø 75 mm)	SPZROB-430	1
Cap for smoke hole (Ø 50 mm)	SPZKIP-170	1
Blocking plug with screws	SPZROB-190	1

Technical details

Technical data	Type / attribute	WKLI20GM
	Color	Black
	Power output	15.7 kW
	Stone sizes	Ø10–15 cm
	Stone amount (kg)	40
Dimensions	Product width	450
	Product height	770
	Product depth (mm)	510
	Net weight (kg)	66
	Gross weight	69
	Package width	515
	Package height	785
	Package depth	460
Connections	Flue connection locations	Back, Top
	Chimney connection diameter	115
Safety and installation dimensions	Safety distance front (non-combustible materials)	500
	Safety distance front (combustible materials)	500
	Safety distance right side (combustible materials)	400
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	400
	Safety distance left side non-combustible materials	100
	Safety distance behind (non-combustible materials)	100
	Safety distance behind (combustible materials)	380
	Safety distance (Ceiling)	1265
	Room min. height(depends on connections and therefore from output, star/delta)	2100